

H85G10AX_ PARTS LIST

| Item | Qty | Part # | Description | Material |
|------|-----|--------------|--------------------------------|---------------|
| 1 | 8 | 6048 | BEARING RETAINER BOLT | MS |
| 2 | 8 | 2247 | LOCKWASHER | MS |
| 3 | 1 | PN1554 | OUTBOARD ISOLATOR | ALUMINUM |
| 4 | 1 | 6256 | O-RING, OUTBOARD ISOLATOR | VITON |
| 5 | 1 | 6094 | BEARING RETAINER (ISOLATOR) | MS |
| 6 | 2 | 3815 | THRUST BEARING | ALLOYED STEEL |
| 7 | 1 | 6093 | G FRAME DRIVE SHAFT (ISOLATOR) | 4140 STEEL |
| 8 | 1 | 3626 | BEARING RETAINER O-RING | VITON |
| 9 | 1 | 6092 | G BEARING FRAME (ISOLATOR) | MS |
| 10 | 1 | 0194 | BEARING FRAME VENT | MS |
| 11 | 2 | 2247 | LOCKWASHER | MS |
| 12 | 2 | 3243 | FRAME FOOT BOLT | MS |
| 13 | 1 | PN1102 | BEARING FRAME FOOT | MS |
| 14 | 1 | 0197 | 1/4 NPT PIPE PLUG | MS |
| 15 | 1 | 6118 | BEARING FRAME O-RING | VITON |
| 16 | 1 | G404-2 | G FRAME SIGHT GLASS ASSEMBLY | BRASS / MS |
| 17 | 1 | 1009 | 1/4 NPT X 4" L PIPE NIPPLE | MS |
| 18 | 1 | 1406 | 2" SNAP RING | SPRING STEEL |
| 19 | 1 | 6158A | RADIAL BEARING | ALLOYED STEEL |
| 20 | 1 | 6086 | SHAFT COUPLER (ISOLATOR) | 316 SS |
| 21 | 1 | 6152 | SHAFT COUPLER KEY | 316 SS |
| 22 | 1 | 0829 | WAVE SPRING (WASHER) | SPRING STEEL |
| 23 | 1 | PN1413 | INBOARD ISOLATOR | ALUMINUM |
| 24 | 1 | 3624 | O-RING, INBOARD ISOLATOR | VITON |
| 25 | 1 | PN1779 | MECHANICAL SEAL HOUSING | 316 SS |
| 26 | 1 | 3624 | O-RING, MECH. SEAL HOUSING | VITON |
| 27 | 1 | 6324 | MECHANICAL SEAL | C/C/V |
| 28 | 1 | 91590A159 | 2-1/4" SNAP RING | 316 SS |
| 29 | 8 | 2593 | 3/8-16 x 1-1/4 HEX BOLT | MS |
| 30 | 8 | 2247 | LOCKWASHER | GRADE 8 STEEL |
| 31 | 1 | PN1780 | CASING ADAPTER | 316 SS |
| 32 | 3 | 1018 | 1/4 NPT PIPE PLUG | 316 SS |
| 33 | 32 | 2593 | 3/8-16 x 1-1/4 HEX BOLT | GRADE 8 STEEL |
| 34 | 32 | 2247 | 3/8 LOCKWASHER | 316 SS |
| 35 | 1 | 3863 | CASING ADAPTER O-RING | VITON |
| 36 | 1 | PER SERIAL # | IMPELLER SHAFT | 316 SS |
| 37 | * | PN1788 | IMPELLER | 316 SS |
| 38 | * | PN1789 | IMPELLER WEDGE | NBR |
| 39 | * | PN1787 | INTERMEDIATE BOWL | NORYL |
| 40 | 1 | PN1782 | UPTHRUST WASHER | DELTRIN |
| 41 | 1 | PN1783 | BEARING RUNNER | A/C/M |
| 42 | 1 | PN1785 | SHAFT END CAP | 316 SS |
| 43 | 1 | 3480 | LOCKWASHER | 316 SS |
| 44 | 1 | 3484 | SHAFT END BOLT | 316 SS |
| 45 | * | 3863 | INTERMEDIATE BOWL O-RING | VITON |
| 46 | 1 | PN1784 | DISCHARGE HOUSING | 316 SS |
| 47 | 1 | PN1786 | FRONT FOOT | MILD STEEL |

T&T PUMP Co. Inc. FAIRMONT, WV 26554

DRAWING TITLE
H85G10AX_ PARTS LIST

CAD FILE
H85G10AX_ EXPLODED VIEW


UNLESS OTHERWISE NOTED
LINEAR DIMS. IN INCHES.
TOLERANCES DECIMAL
.XXX+/-
XXX+/-
DO NOT SCALE DRAWING
DRAWING NO.

ANGULAR
DIMENSIONS
+/-

DWG. SIZE
A

SCALE NONE
RELEASE DATE 7-06-09
SHEET 1 OF 1

DRAWN CWR 7-06-09
CHECK
DESIGN
ENGR



* DETERMINED BY # OF STAGES