



MODEL NUMBER	DISC.	INLET	A	B	C
ST7MB85X18G20A	3" V.I.C.	3" V.I.C.	106.85	11.875	8.625
ST7MB85X18G25A	3" V.I.C.	3" V.I.C.	109.35	11.875	8.625
ST7MB85X19G25A	3" V.I.C.	3" V.I.C.	111.65	11.875	8.625
ST7MB85X20G25A	3" V.I.C.	3" V.I.C.	114.05	11.875	8.625
ST7MB85X20G30A	3" V.I.C.	3" V.I.C.	116.65	11.875	8.625
ST7MB85X21G25A	3" V.I.C.	3" V.I.C.	116.45	11.875	8.625
ST7MB85X21G30A	3" V.I.C.	3" V.I.C.	119.05	11.875	8.625
ST7MB85X22G25A	3" V.I.C.	3" V.I.C.	118.85	11.875	8.625
ST7MB85X22G30A	3" V.I.C.	3" V.I.C.	121.45	11.875	8.625
ST7MB85X23G30A	3" V.I.C.	3" V.I.C.	123.85	11.875	8.625
ST7MB85X24G30A	3" V.I.C.	3" V.I.C.	126.25	11.875	8.625
ST7MB85X24G40A	3" V.I.C.	3" V.I.C.	131.35	11.875	8.625
ST7MB85X25G30A	3" V.I.C.	3" V.I.C.	128.55	11.875	8.625
ST7MB85X25G40A	3" V.I.C.	3" V.I.C.	133.65	11.875	8.625
ST7MB85X26G30A	3" V.I.C.	3" V.I.C.	130.95	11.875	8.625
ST7MB85X26G40A	3" V.I.C.	3" V.I.C.	136.05	11.875	8.625
ST7MB85X27G30A	3" V.I.C.	3" V.I.C.	133.35	11.875	8.625
ST7MB85X27G40A	3" V.I.C.	3" V.I.C.	138.45	11.875	8.625
ST7MB85X28G40A	3" V.I.C.	3" V.I.C.	140.85	11.875	8.625
ST7MB85X29G40A	3" V.I.C.	3" V.I.C.	143.25	11.875	8.625
ST7MB85X30G40A	3" V.I.C.	3" V.I.C.	145.55	11.875	8.625
ST7MB85X33G40A	3" V.I.C.	3" V.I.C.	162.45	11.875	8.625
ST7MB85X33G50A	3" V.I.C.	3" V.I.C.	179.45	11.875	8.625

- NOTES:
- DIMENSIONS ARE IN INCHES.
 - PUMP INLET WILL MATE WITH VICTAULIC TYPE CLAMPED UNION. DISCHARGE WILL MATE WITH VICTAULIC TYPE CLAMPED UNION.
 - DO NOT OPERATE OUTSIDE THE DESIGNATED FLOW RANGE.
 - 20 PSI MINIMUM INLET PRESSURE IS REQUIRED. PUMP MUST BE COMPLETELY FLOODED BEFORE OPERATING. DO NOT OPERATE PUMP DRY, OPERATING WITH IN THE DESIGNATED FLOW RANGE WILL INSURE ADEQUATE FLOW PAST THE MOTOR FOR COOLING. WATER TEMP NOT TO EXCEED 85°F.
 - TO ACCOMPLISH CORRECT ROTATION, INTERCHANGE ANY TWO MOTOR LEADS, THEN COMPARE WATER QUANTITY AND DEVELOPED PRESSURE. THE WIRE CONNECTION THAT DEVELOPS THE HIGHEST FLOW AND PRESSURE IS THE CORRECT ONE.
 - UNIT MUST BE PROPERLY GROUNDED. FAILURE TO DO SO MY RESULT IN SERIOUS ELECTRICAL SHOCK. MOTOR MUST BE GROUNDED IN ACCORDANCE TO NATIONAL AND LOCAL CODES.
 - REFER TO THE OPERATION AND MAINTAINANCE MANUAL FOR ADDITIONAL OPERATIONAL INSTRUCTIONS.
 - SPECIAL MECHANICAL MODIFICATIONS MAY SUPERSEDE DIMENSIONS WHICH ARE A FUNCTION OF THE MODIFICATION.



T&T PUMP CO.

DRAWING NO. 	DRAWING TITLE S77MB85 60HZ SHEET 2
DRAWN BY: CHECKED BY: DESIGN BY: ENGR. BY:	CAD FILE: S77MB85 CATALOG DRWS. DWG SCALE: A RELEASE DATE: 1-1-88 SHEET: 2 OF 2

T&T PUMP CO. INC. FAIRMONT, WV 26554